



## Contact Us

Office : 256.776.7786  
Email : [sales@firetruckmall.com](mailto:sales@firetruckmall.com)  
Website: [www.firetruckmall.com](http://www.firetruckmall.com)

15410 US Highway 231,  
Union Grove, AL 35175  
Stock #: 21133  
Price: \$120,000

2022 Hytrans HydroSub

☐ 2022 Hytrans HydroSub

☐ Driver's Side Discharges: (1) 4" Storz

☐ Other Chassis

☐ Hatz 55KW Diesel Generator

☐ 1500 GPM Pump

☐ Engine Hours: 1,3.4

○ Additional equipment not included with purchase unless otherwise listed. Mileage readings may not be real-time and should be confirmed.

○ Length: 20' 2"

○ **Condition: like new**

**Hours: 13.5**

The HydroSub 60 is a mobile pump unit driven by a powerful diesel engine with radiator cooling. It consists of a diesel-hydraulic power pack pump unit with a portable hydraulic driven submersible pump. [Hytrans | HydroSub 60 | Hydraulically driven pump unit](#)

### **Design**

The unit is compactly built in a skid-frame with light weight side panels and an anodized aluminium door. The unit is mounted to a tandem axle flat deck trailer with tool boxes for equipment storage. Inside the frame there is a storage space for either the standard submersible pump or the optionally available Flood Pump, not included.

The submersible pump will not be affected by waves or shallow water levels. Even in cases where there is a risk of an airlock due to an air bubble, the pump will maintain its operation.

### **Quick access to open water**

The 30 meter hydraulic hose length guarantees access to almost all open waters without any capacity loss and has a reach up to 30 meter either vertical, horizontal or a combination of both.

### **Hydraulic power for powerful performance**

What sets Hytrans apart is our hydraulically driven submersible pump technology. These powerful pumps allow firefighters to draw water from sources far away, overcoming the limitations of conventional systems. By utilizing hydraulic power, our pumps maintain their capacity and efficiency, delivering continuous high-volume water supplies over long distances. This ensures that firefighters can focus on controlling the fire, knowing that their water supply will remain uninterrupted, even in extreme conditions.

### ***High-capacity dewatering systems***

When floods threaten communities, emergency teams need powerful, rapidly deployable dewatering systems to take immediate action. Hytrans mobile water transport systems are engineered for high performance and fast deployment, becoming operational within minutes of arrival with minimal manpower. Unlike conventional suction pumps, Hytrans systems combine unmatched speed, capacity, mobility, and flexibility, ensuring a rapid response when every second counts.

Designed specifically for high-volume flood control, our innovative flood solutions integrate optimized Hytrans Flood Pumps—each capable of pumping 20,000 liters per minute (lpm). Including lightweight, dedicated Hytrans Flood Hoses to efficiently transfer water over the first water barrier, typically located nearby. Hytrans offers scalable solutions ranging from 20,000 lpm to 130,000 lpm (34,000 GPM), with the ability to deploy multiple systems simultaneously for even greater capacity when needed.

### ***Continuous, nearby water supply in remote locations***

Hytrans leverages hydraulically driven pumps to create a continuous, high-capacity water supply near the wildfire, eliminating the need for long-distance water refill runs. With an open or closed relay setup, our systems can transport water across tens of kilometers, even uphill, ensuring reliable access in the most remote and rugged terrains.

By bringing the water source closer, helicopters and ground vehicles can refill faster, drastically reducing travel times and increasing water supply rates. The result? Greater operational efficiency, faster wildfire suppression, and minimized damage — allowing response teams to act with speed and precision when every second counts.

### ***Capacity***

|                                                                                         |                                                                              |                                                                                   |
|-----------------------------------------------------------------------------------------|------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Standard<br>impeller:<br>1.500 lpm (optional):<br>at 9,5 bar<br>(400 GPM<br>at 138 psi) | Hi-Flow<br>impeller<br>4.000 lpm<br>at 2,5 bar<br>(1050<br>GPM at<br>35 psi) | Flood<br>Pump (optiona<br>20.000<br>lpm at 0,3<br>bar (5300<br>GPM at<br>4.3 psi) |
|-----------------------------------------------------------------------------------------|------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|

### ***Control instruments***

|                                                                                    |                                                                                                                                                            |                                                                                                                |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Hytrans<br>control<br>system                                                       | Vital<br>parameters<br>are<br>monitored<br>and<br>logged<br>(e.g. oil<br>pressure,<br>oil<br>temperature,<br>fuel level,<br>motor<br>temperature,<br>etc.) | Audible<br>and<br>visible<br>alarms are<br>generated<br>when a<br>parameter<br>falls<br>outside its<br>setting |
| Machine<br>status<br>light,<br>surround<br>illumination<br>and<br>working<br>light | Automatic<br>water<br>pressure<br>regulation<br>(option)                                                                                                   |                                                                                                                |

### ***The HydroSub 60 can be used for:***

|                                              |                                                    |                     |
|----------------------------------------------|----------------------------------------------------|---------------------|
| Large<br>scale<br>firefighting<br>Dewatering | Flood<br>control<br>Emergency<br>back up<br>supply | Wildfire<br>control |
|----------------------------------------------|----------------------------------------------------|---------------------|

### ***Capacity***

|                                                    |                                                                                                               |                                                                               |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| 400 GPM<br>@ 138<br>PSI (1500<br>LPM @<br>9,5 bar) | Optional<br>Hi-Flow<br>impeller<br>(not<br>included)<br>1050<br>GPM @<br>35 PSI<br>(4000<br>LPM @<br>2,5 bar) | Optional<br>flood<br>pump (not<br>included)<br>5300<br>GPM<br>(20,000<br>LPM) |
| Pump lift<br>30 meters                             |                                                                                                               |                                                                               |

### ***Maintenance***

Regularly  
maintained  
by District  
of North  
Vancouver  
fleet  
maintenance.



Brindlee Mountain Fire Apparatus is one of the world's largest used fire truck sales and service companies. Based just outside of Huntsville, Alabama, the company has forty-five full-time personnel occupying over 12,000 square feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at [www.firetruckmall.com](http://www.firetruckmall.com)